

# GE 230V

## Automatic Power Factor Correction equipment



**GE 230V** series is particularly suitable for three-phase networks with **low harmonic distortion** in current. These equipment guarantee an accurate power factor correction, thanks to a multi-step design that effectively divides the power. In addition, on the G6E cabinet, all the capacitors banks are assembled on racks, easily removable from the front of the panel, for simple management and maintenance.

### PERFORMANCE DATA

■ Rated voltage	230 Vac (others on request)
■ Rated frequency	50 Hz (60 Hz on request)
■ Insulation voltage	690 Vac
■ Auxiliary voltage	230 Vac (110 Vac on request)
■ Overvoltage	1,1 Un (rated voltage)
■ Temperature range	-5 / +40 °C
■ Impulse withstand	6 kV (G3E, G4E); 8 kV (G4RM, G6E)

### HARMONIC CONTENT (in the absence of resonance)

THD(I)max. = 15%	on the network
THD(Ic)max. = 50%	on the capacitors

### TECHNICAL DATA

<b>Enclosures</b>	Made of sheet steel, protected against corrosion by phosphating and epoxy powder coating. RAL 7035 colour (others on request). Degree of protection: external panel IP 31, with the exception of type G3E and G4E with IP30 (others on request); internal panel IP 20 at the input of power cables (IP 20 with open doors on request).
<b>Installation</b>	Indoor installation, in a well ventilated position away from heat sources.
<b>Ventilation</b>	Natural for powers up to 95 kvar; Forced for powers over 95 kvar.
<b>Switch isolator</b>	Tri-polar off-load disconnecter.
<b>Wiring</b>	The internal connections are made with flame retardant cables with very low smoke emission (other types of cables on request). On the non-pre-insulated terminals the connection point is covered with a long-life heat-shrinking sheath. The auxiliary voltage are appropriately identified in compliance with current regulations.
<b>3-pole contactors</b>	Each battery is switched on / off by a three-pole contactor (Class AC6-b) to offer high reliability. The limitation of current peaks caused by the insertion of the capacitive batteries is guaranteed by pre-charging resistors.
<b>Fuses</b>	Each capacitors bank is protected by fuses. The protection system of both the power circuits (NH-00 curve gG fuses) and the auxiliary ones (isolable fuse holders and 10.3x38 fuses) foresees the use of high breaking power fuses (100kA).
<b>Capacitors</b>	Single-phase capacitors in self-healing metallized polypropylene (MKP), equipped with an anti-burst device and discharge resistance. They are impregnated in vegetable oil, PCB free. Delta connection. Type of continuous service. <ul style="list-style-type: none"><li>• rated voltage: 250 Vac (maximum voltage 275 Vac)</li><li>• overvoltage: 1.1 x A (8h / 24h)</li><li>• current overload: 1.3 x In</li><li>• capacity tolerance: -5% / + 10%</li><li>• losses due to dissipation: <math>\leq 0.4</math> W / kvar</li><li>• temperature category: -25 / D</li></ul>
<b>Controller</b>	<ul style="list-style-type: none"><li>• type of measurement: varmetric.</li><li>• amperometric signal: by means of an amperometric transformer with secondary 5A, class 1 - 5VA (by the user)</li><li>• amperometric signal sensitivity: 2.5% for BMR series, 0.3% for HPR series</li><li>• standard capacitors on / off times: 25 " <math>\div</math> 30" (others on request)</li></ul>

### QUALITY AND TESTING

<b>Regulations</b>	Capacitors: IEC/EN 60831-1 / 2 certified by IMQ (V1927); Equipment: IEC/EN 61439-1 / 2, IEC/EN 61921.
<b>European directives</b>	Low voltage: 2014/35/CE; Electromagnetic compatibility: 2014/30/CE.
<b>Testing</b>	100% of the automatic equipment is subject to visual inspection, insulation test: phase-phase and phase-earth, battery efficiency and ventilation circuit control: the report is included in the documentation. The capacitors are tested in three consecutive stages of the production process: after winding, regeneration and before labeling.

### CONFIGURATION


#### General notes

- For dimensions, please consult the cabinet drawings, referring to the "Type" column.
- The indication for cable entry (power supply) is as follows: ↑ from the bottom, ↙ side up, ↓ from the top
- The rated power is expressed at 230 V - 50 Hz.

The choice of supply cables depends on the installation conditions, the length of the same and the ambient temperature. For a correct sizing, refer to the IEC 60364-5, CEI 64-8 and the UNEL 35024/01 standards.

#### Cloud Control System (CCS)






The symbol  indicates that CCS, the remote monitoring system, is pre-installed on the P.F.C. equipment. For any specific information, and to find out the advantages of the Cloud Control System service, refer to the appropriate brochure available on [www.comarcond.com](http://www.comarcond.com) or directly on request.



#### Table

THD(I)max. = 15%

THD(Ic)max. = 50%

Code	Type	Qn (kvar)	Cable entry	In (A)	Banks size (kvar)				Steps (n)	Switch isolator (A)	Controller (type)	CCS	Weight (kg)
8571232125108	G3E	12,5	↙	31	2,5	5	5		5	80	BMR6		16
8571232175100	G3E	17,5	↙	44	2,5	5	10		7	80	BMR6		23
8571232250100	G3E	25	↙	62	5	10	10		5	125	BMR6		26
8571232375108	G4E	37,5	↙	94	2,5	5	10	20	15	200	BMR6		46
8571232550208	G4RM	55	↙	138	5	10	20	20	11	200	BMR6		89
8571232750208	G4RM	75	↙	188	5	10	10	10	20	20	BMR6		95
8571232950208	G4RM	95	↙	238	5	10	20	20	20	20	BMR6		102
8571233115209	G6E	115	↓	288	5	10	20	20	20	40	HPR6		175
8571233140209	G6E	140	↓	351	10	10	20	20	40	40	HPR6		192
8571233160209	G6E	160	↓	401	20	20	20	20	40	40	HPR6		207
8571233180209	G6E	180	↓	452	20	20	20	40	40	40	HPR6		240
8571233200209	G6E	200	↓	502	20	20	40	40	40	40	HPR6		255

Other solutions are available on request.