TECHNICAL DATA COMMON TO ALL SERIES IN STANDARD CONFIGURATION

Enclosure	Made of steel sheet, protected against corrosion by phosphating and epoxy powder coating. Colour RAL 7035. Segregazione: form 1 External degree of protection: panel type G3E, G4E IP30; G4RM IP40; G6E, G8E, G9E IP31 Internal degree of protection: panels with interlocked switch-disconnector IP20 on live parts; IP 20 protection in additional modules In the G6, G8 and G9 cabinets, capacitor banks are assembled on drawers that can be pulled out from the front of the cabinet for quick maintenance G6, G8, G9 cabinets are equipped with eyebolts for lifting
Installation	Indoor installation, in a well ventilated position free from solar radiation. Pollution degree 1 Working temperature: -5 / +40 °C; Relative humidity RH50% @40°C Altitude: <1000 asl
Main Disconnector	Three-phase off-load disconnector with mechanical door interlock.
Wiring	Power connections are made with FS17-450/750V insulated, flame-retardant low smoke emission cables. On non-preinsulated cable lugs, the connection point is covered with a durable heat-shrink sleeve. Auxiliary circuits are appropriately identified in accordance with current standards.
Bank insertion	The banks are driven by three-phase contactors (Class AC6-b). Series without tuning reactor have contactors with a pre-insertion resistor to limit peak inrush current Static insertion series are fitted with thyristor insertion modules controlled by microprocessor such that switching on/off occurs when the potential difference between the mains and the capacitors is zero. (zero crossing). The switching time for the insertion of the capacitor banks is approximately 200 ms.
Fuses	The capacitive banks are protected by high breaking capacity fuses (100kA). The protection system for the power circuits uses NH-00 curve gG fuses; for the auxiliary circuits sectionable fuse holders and 10.3x38 fuses.
Auxiliary circuits	400 Vac for G3E, G4E, G4RM 230 Vac for G6E, G8E, G9E Internal transformer
Impulse withstand	6 kV for type G3E, G4E; 8 kV for G4RM, G6E, G8E, G9E
Capacitors	Single-phase capacitors made of self-healing (SH) metallised polypropylene (MKP) Over pressure safety device — Discharge resistor (75V within 3') PCB-free vegetable oil impregnation — Delta connection. Continuous service — Overvoltage: 1.1 x Un (8h / 24h) Current overload: 1.3 x In — Capacitance tollerance: -5% / +10% Dissipation losses: ≤0.4 W/kvar — Temperature category: -25 / D In the higher-performance series, **'Heavy Duty'** capacitors made of high thickness film and multiple elements in series are installed to reduce the effect of high currents on the element heads
Tuning reactor (where present)	Iron core with oriented crystals; aluminium windings Resin impregnation Dissipation loss (average): 6W/kvar Over-temperature control probe
Controller	Electronic, measurement type: varmetric on 4 quadrants. Current signal: via current transformer (user-supplied) with 5A secondary, class 1 Current signal sensitivity: 2.5% for BMR series, 0.3% for HPR series
Ventilation	Natural for series without de-tuning chokes and power below 200 kvar. Forced by high-efficiency fans with top expulsion for all other equipment
CCS	remote monitoring system for real time data display, emailing of alarms, historical data storage. Included on DMP-FTV, AAR/6, AAR/D20 series; on request on other series The symbol indicates that the equipment is equipped with CCS The symbol indicates that the CCS system is installable on the equipment
Safety	Automatic equipment shut-down in case of high THD(I), over-temperature >50°C, under and overvoltage. Bank shut down for reactor overtemperature (where fitted) Dry contact NC for extreme internal temperature (>70°C) In addition on HPR controller: auto shut-down for high THD(U), loss of capacitance of the bank
Testing	100% of the equipment undergoes visual inspection, phase-to-phase and phase-to-ground insulation tests, bank efficiency and ventilation circuit checks. Capacitors are tested for capacitance, dissipation factor [tan(δ)], verification of insulation to earth and overvoltage resistance at three consecutive points of the production process: after winding, during ageing process and at final assembly
Regulation	Capacitors: IEC/EN 60831-1 / 2 certified by IMQ (V1927) Equipment: IEC/EN 61439-1 / 2, IEC/EN 61921; 2014/35/EC Electromagnetic compatibility: 2014/30/EC.



The DMP-FTV series are suitable for three-phase networks with an operating voltage of **400 Vac** and **medium to high harmonic** current **content**. They are suitable for small generation systems (FTV or other) and continuous duty cycles. The use of Heavy Duty double-element technology increases capacitor life even in harsh situations

PERFORMANCE DATA

- **Rated voltage** 415 Vac (others on request)
- **Rated frequency** 50 Hz (60 Hz on request)
- **Insulation voltage** 800 Vac
- **Voltage overload** 1.1 Un (rated voltage)
- **Capacitors** Un=550; Umax 600

HARMONIC CONTENT
RESONANCE NOT ADMITTED

THD(I)max. = 40 % in the grid

THD(Ic)max. = 90 % on capacitors

STANDARD CONFIGURATIONS

Code	Type	Qn (kvar)	Cable entry	In (A)	bank power (kvar)	Steps (n)	Disconnector (A)	Controller (type)	CCS	Weight (kg)
8881412225500	G3E	22,15	↙	31	3,4+6,25+12,5	7	80	BMR6		15
8881412310500	G3E	31,25	↙	43	6,25+2x12,5	5	80	BMR6		18
8881412435500	G3E	43,75	↙	61	6,25+12,5+25	7	100	BMR6		22
8881412500500	G3E	50	↙	70	2x12,5+25	4	100	BMR6		23
8881412625500	G3E	62,5	↙	87	12,5+2x25	5	160	BMR6		26
8881412750500	G4E	75	↙	104	2x12.5+2x25	6	200	BMR6		38
8881413100500	G4E	100	↙	139	2x12,5+25+50	8	200	BMR6		46
8881413125500	G4RM	125	↙	174	2x12.5+2x50	5	250	BMR6		83
8881413150500	G4RM	150	↙	209	2x25+2x50	6	315	BMR6		84
8881413175500	G4RM	175	↙	243	25+3x50	7	400	BMR6		87
8881413200500	G4RM	200	↙	278	2x25+50+100	8	400	BMR6		89
8881413225500	G4RM	225	↙	313	25+2x50+100	9	500	BMR6		95
8881413250500	G4RM	250	↙	348	25+50+75+100	10	500	BMR6		102
888141000045R	G6E	300	↓	417	25+50+3x75	12	630	HPR6	🖧	175
888141005045R	G6E	350	↓	487	50+4x75	7	800	HPR6	🖧	192
888141340045R	G6E	400	↓	556	2x50+4x75	8	800	HPR6	🖧	207
888141345045R	G6E	450	↓	626	3x50+2x75+150	9	1000	HPR6	🖧	240
888141350045R	G6E	500	↓	696	50+4x75+150	10	1000	HPR6	🖧	255
888141360050R	G8E	600	↑	836	8x75	8	1250	HPR12	🖧	330
888141365050R	G8E	650	↑	904	50+6x75+150	11	1600	HPR12	🖧	345
888141375050R	G8E	750	↑	1045	6x75+2x150	10	1600	HPR12	🖧	380
888141382550R	G8E (II)	825	↑	1149	5x75+3x150	11	800+1000	HPR12	🖧	510
888141390050R	G8E (II)	900	↑	1254	4x75+4x150	12	1000+1000	HPR12	🖧	530

Note

For dimensions, please refer to the mechanical drawings section, referring to the 'Type' column.

- The cable entry (power supply) legend is as follows: ↑ from below, ↙ side up, ↓ from above,
- Rated power is expressed at rated voltage (Un)
- 🖧 indicates that the equipment is equipped with CCS
- 🛠 indicates that the CCS system is installable on the equipment